Date Prepared: 1.6.06

MATERIAL SAFETY DATA SHEET IN COMPLIANCE WITH OCCUPATIONAL SAFETY AND HEALTH

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

MANUFACTURER'S NAME THE WISEMAN GROUP - MANUFACTURING CHEMISTS	TELEPHONE NO +44 1277 633200
ADDRESS POBOX 58, HIGH STREET, INGATESTONE, ESSEX. CM4 9DL, ENGLAND	PRODUCT NAME EVERFLUX
FORMULA MIXTURE	GENERAL USE SOLDERING FLUX FOR COPPER, BRASS, TIN & STEEL

SECTION II - HAZARDOUS INGREDIENTS

CHEMICAL PRODUCT & CODE		%	TLV (UNITS)
ZINC CHLORIDE	CAS NO 7646-85-7	- 4	1 mg/m ³
AMMONIUM CHLORIDE	CAS NO 12125-02-09	2	10 mg/m ³

SECTION III - PHYSICAL DATA

BOILING POINT (°F)	695 ⁰	SPECIFIC GRAVITY	1.4
VAPOUR PRESSURE (mm Hg)	< 1	PERCENT, VOLATILE BY VOLUME	NIL
VAPOUR DENSITY (AIR = 1)	>1	EVAPORATION RATE	<< 1
SOLUBILITY IN WATER	> 99%		
APPEARANCE AND ODOR	WHITE, O	DOURLESS PASTE	

SECTION IV - FIRE & EXPLOSION HAZARD DATA

FLASH POINT	NON FLAMMABLE
EXTINGUISHING MEDIA	IF INVOLVED IN FORE USE WATER
SPECIAL FIREFIGHTING PROCEDURES	N/A
UNUSUAL FIRE AND EXPLOSION HAZARDS	N/A

Date Prepared: 1.6.06

SECTION V - HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE 1 mg/M³ (TWA:8 Hr)

EFFECTS OF OVER EXPOSURE

MAY CAUSE IRRITATION AND INFLAME SKIN AND EYES

EMMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT - IRRIGATE FOR 15 MINUTES UNDER RUNNING COLD TAP, SEEK MEDICAL ATTENTION IF IRRITATION DEVELOPS

SKIN CONTACT - WASH WITH PLENTY OF SOAP AND WATER

INGESTION - DO NOT INDUCE VOMITING, DRINK BICARBONATE OF SODA IN WATER / WASHING SODA IN WATER FOLLOWED BY MILK - SEEK MEDICAL ATTENTION

HMIS RATING

HEALTH O, FLAMMABILITY O, REACTIVITY O

SECTION VI - REACTIVITY DATA

STABILITY	STABLE :
INCOMPATABILITY (MATERIALS TO AVOID)	OXIDIZING AGENTS
HAZARDOUS DECOMPOSITION PRODUCTS	BY THERMAL -CO2, CL, NH3
HAZARDOUS POLYMERIZATION	NIL.

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILT SMALL SPILL – WIPE UP, WASH REMAINDER WITH WATER TO DRAIN LARGE SPILL – CONTAIN SPILL, SCRAPE UP FOR RE-USE OR SOAK WITH ABSORBENT MATERIAL, FLUSH REMAINDER WITH WATER

WASTE DISPOSAL METHOD DISPOSE OF IN ACCORDANCE WITH APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS

SECTION VIII - SPECIAL PROTECTION INFORMATION

VENTILATION NORMAL ROOM VENTILATION, LOCAL EXHAUST IN CONFINED AREAS

SKIN PROTECTION

GLOVES RECOMMENDED TO PROTECT FROM SOLDER BURNS

EYE PROTECTION

FACE VISOR/GOGGLES RECOMMENDED TO PROTECT FROM SOLDER BURNS

OTHER PROTECTIVE EQUIPMENT

EYE WASH, GAS RESPIRATOR IN VERY ENCLOSED AREAS

Date Prepared: 1.6.06

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING PREVENT EYE CONTACT, AVOID SKIN CONTACT, KEEP CONTAINER UPRIGHT

OTHER PRECAUTIONS
KEEP CONTAINER CLOSED WHEN NOT IN USE, STORE OUT OF REACH OF CHILDREN

SECTION X - REGULATORY INFORMATION

OSHA Hazard Status: this product is not considered to be hazardous as defined by the US osha HCS (29 CFR 1910:1200)

UK Manufacturers of Radiators MARC solubility test approved.
Everflux is UK WRAS approved as to effects on water quality.
American Society for Testing Materials (ASTM): Everflux meets ASTM specification B 813
Copper Development Association (CDA): Everflux meets test method 1.0
Everflux is approved for use where US states enforce the Uniform Plumbing Code and/or the International Plumbing Code.

This Material Safety Data Sheet is laid out in accordance and complies with the criteria of the US OSHA Hazard Communication Standard and the Canadian WHMIS Controlled Product Regulations.

SECTION XI - OTHER INFORMATION

The information contained herein is based on data available to us and is accurate and reliable to the best of our knowledge and belief. However, the Wiseman Group makes no representations as to its completeness or accuracy. Information is supplied on condition that persons receiving such information will make their own determination as to its suitability for their purposes prior to use. In no event will the Wiseman Group be responsible for damages of any nature whatsoever resulting from the use of or reliance upon the information contained herein.