

MOBILTEMP SHC 32

640219-00

1. PRODUCT AND COMPANY IDENTIFICATION APPROVAL DATE: 10/28/96 PRODUCT NAME: MOBILTEMP SHC 32 SUPPLIER: MOBIL OIL CORP. AMERICAS MARKETING AND REFINING 3225 GALLOWS RD. FAIRFAX, VA 22037 24 - Hour Emergency (call collect): 609-737-4411 Product and MSDS Information: 800-662-4525 703-849-5700 CHEMTREC: 800-424-9300 202-483-7616 2. COMPOSITION/INFORMATION ON INGREDIENTS CHEMICAL NAMES AND SYNONYMS: SYN. HYDROCARBONS AND ADDITIVES INGREDIENTS CONSIDERED HAZARDOUS TO HEALTH: Substance Name ACETONE (67-64-1) 1-5 PENTAERYTHRITOL (115-77-5) See Section 15 for European Label Information. See Section 8 for exposure limits (if applicable). 3. HAZARDS IDENTIFICATION US OSHA HAZARD COMMUNICATION STANDARD: Product assessed in accordance with OSHA 29 CFR 1910.1200 and determined not to be hazardous. EFFECTS OF OVEREXPOSURE: No significant effects expected. EMERGENCY RESPONSE DATA: Red Grease. DOT ERG No. - NA 4. FIRST AID MEASURES EYE CONTACT: Flush thoroughly with water. If irritation occurs, call a physician. SKIN CONTACT: Wash contact areas with soap and water. High pressure accidental injection through the skin requires immediate medical attention for possible incision, irrigation and/or debridement. INHALATION: Not expected to be a problem. INGESTION: Not expected to be a problem. However, if greater than 1/2 liter(pint) ingested, immediately give 1 to 2 glasses of water and call a physician, hospital emergency room or poison control center for assistance. Do not induce vomiting or give anything by mouth to an unconscious person. ______ 5. FIRE-FIGHTING MEASURES _____ EXTINGUISHING MEDIA: Carbon dioxide, foam, dry chemical and water fog. SPECIAL FIRE FIGHTING PROCEDURES: Water or foam may cause frothing. Use water to keep fire exposed containers cool. Water spray may be used to flush spills away from exposure. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply.

SPECIAL PROTECTIVE EQUIPMENT: For fires in enclosed areas, fire

fighters must use self-contained breathing apparatus.

UNUSUAL FIRE AND EXPLOSION HAZARDS: None. Flash Point C(F): >

204(400) (ESTIMATED (OIL COC)). Flammable limits - LEL: NA,

UEL: NA.

NFPA HAZARD ID: Health: 0, Flammability: 1, Reactivity: 0
HAZARDOUS DECOMPOSITION PRODUCTS: Nitrogen oxides. Phosphorus oxides.
Carbon monoxide.

6. ACCIDENTAL RELEASE MEASURES

NOTIFICATION PROCEDURES: Report spills as required to appropriate authorities. U. S. Coast Guard regulations require immediate reporting of spills that could reach any waterway including intermittent dry creeks. Report spill to Coast Guard toll free number (800) 424-8802. In case of accident or road spill notify CHEMTREC (800) 424-9300.

PROCEDURES IF MATERIAL IS RELEASED OR SPILLED: Shovel up and dispose of at an appropriate waste disposal facility in accordance with current applicable laws and regulations, and product characteristics at time of disposal.

ENVIRONMENTAL PRECAUTIONS: Prevent spills from entering storm sewers or drains and contact with soil.

PERSONAL PRECAUTIONS: See Section 8

7. HANDLING AND STORAGE

TYPING TITE THE STATE OF THE ST

HANDLING: High pressure injection under the skin may occur due to the rupture of pressurized lines. Always seek medical attention.

STORAGE: Do not store in open or unlabelled containers. Store away from strong oxidizing agents or combustible material.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

VENTILATION: No special requirements under ordinary conditions of use and with adequate ventilation.

RESPIRATORY PROTECTION: No special requirements under ordinary conditions of use and with adequate ventilation.

EYE PROTECTION: Generally eye contact is unlikely with this type material. If eye contact is likely, safety glasses with side shields or chemical type goggles should be worn.

SKIN PROTECTION: If prolonged or repeated skin contact is likely, oil impervious gloves should be worn. Good personal hygiene practices should always be followed.

	T'WA	STEL NOTE	ı
Source	ppm mg/m3	ppm mg/m3	
MOBIL	688 1633		
OSHA	750 1800	1000 2400	
ACGIH	500 1188	750 1782	
MOBIL	10		
OSHA	5		
OSHA	10		
ACGIH	10		
	MOBIL OSHA ACGIH MOBIL OSHA OSHA	Source ppm mg/m3 MOBIL 688 1633 OSHA 750 1800 ACGIH 500 1188 MOBIL 10 OSHA 5 OSHA 10	MOBIL 688 1633 OSHA 750 1800 1000 2400 ACGIH 500 1188 750 1782 MOBIL 10 OSHA 5 OSHA 10

NOTE: Limits shown for guidance only. Follow applicable regulations.

9. PHYSICAL AND CHEMICAL PROPERTIES

Typical physical properties are given below. Consult Product Data Sheet for specific details.

APPEARANCE: Grease

COLOR: Red ODOR: Mild

```
ODOR THRESHOLD-ppm: NE
pH: NA
BOILING POINT C(F): > 316(600)
DROP POINT C(F): NA
FLASH POINT C(F): > 204(400) (ESTIMATED (OIL COC))
FLAMMABILITY: NE
AUTO FLAMMABILITY: NE
EXPLOSIVE PROPERTIES: NA
OXIDIZING PROPERTIES: NA
VAPOR PRESSURE-mmHg 20 C: < 0.1
VAPOR DENSITY: NE
EVAPORATION RATE: NE
RELATIVE DENSITY, 15/4 C: 0.952
SOLUBILITY IN WATER: Negligible
PARTITION COEFFICIENT: NE
VISCOSITY AT 40 C, cSt: NE
VISCOSITY AT 100 C, cSt: NE
POUR POINT C(F): NE
FREEZING POINT C(F): NE
VOLATILE ORGANIC COMPOUND: NA
NOTE: MOST PHYSICAL PROPERTIES FOR OIL COMPONENT.
          NA=NOT APPLICABLE NE=NOT ESTABLISHED D=DECOMPOSES
FOR FURTHER TECHNICAL INFORMATION, CONTACT YOUR MARKETING REPRESENTATIVE
10. STABILITY AND REACTIVITY
   ______
STABILITY (THERMAL, LIGHT, ETC.): Stable.
CONDITIONS TO AVOID: Extreme heat.
INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizers.
HAZARDOUS DECOMPOSITION PRODUCTS: Nitrogen oxides. Phosphorus oxides.
    Carbon monoxide.
HAZARDOUS POLYMERIZATION: Will not occur.
11. TOXICOLOGICAL DATA
---ACUTE TOXICOLOGY---
ORAL TOXICITY (RATS): Practically non-toxic (LD50: greater than 2000
    mg/kg). ---Based on testing of similar products and/or the
    components.
DERMAL TOXICITY (RABBITS): Practically non-toxic (LD50: greater than
    2000 mg/kg). ---Based on testing of similar products and/or the
    components.
INHALATION TOXICITY (RATS): Not applicable ---Harmful concentrations
    of mists and/or vapors are unlikely to be encountered through any
    customary or reasonably foreseeable handling, use, or misuse of
    this product.
EYE IRRITATION (RABBITS): Practically non-irritating. (Draize score:
     0 or greater but 6 or less). ---Based on testing of similar
    products and/or the components.
SKIN IRRITATION (RABBITS): Practically non-irritating. (Primary
    Irritation Index: 0.5 or less). ---Based on testing of similar
    products and/or the components.
                --- SUBCHRONIC TOXICOLOGY (SUMMARY) ---
Representative Mobil formulations have been tested at the Mobil
     Environmental and Health Sciences Laboratory by dermal
     applications to rats 5 days/week for 90 days at doses
     significantly higher than those expected during normal industrial
     exposure. Extensive evaluations, including microscopic
     examination of internal organs and clinical chemistry of body
     fluids, showed no adverse effects.
                 ---CHRONIC TOXICOLOGY (SUMMARY)---
Representative Mobil formulations have not caused skin sensitization
     in humans.
```

---OTHER TOXICOLOGY DATA---

This product is formulated with a | (()) synthetic hydrocarbon as the base stock. The Mobil Environmental and Health Sciences Laboratory has tested representative () synthetic base stocks to assess their potential adverse effects on human health. Assessment of human health effects was based on acute oral, dermal, and inhalation toxicity; eye and skin irritation; subchronic dermal toxicity and reproductive studies; guinea pig sensitization; and mutagenicity and chromosomal damage assays. None of these base stocks appears to pose a health hazard to humans under conditions of expected 12. ECOLOGICAL INFORMATION ENVIRONMENTAL FATE AND EFFECTS: Not established. 13. DISPOSAL CONSIDERATIONS WASTE DISPOSAL: Product is suitable for burning in an enclosed, controlled burner for fuel value or disposal by supervised incineration. Such burning may be limited pursuant to the Resource Conservation and Recovery Act. In addition, the product is suitable for processing by an approved recycling facility or can be disposed of at an appropriate government waste disposal facility. Use of these methods is subject to user compliance with applicable laws and regulations and consideration of product characteristics at time of disposal. RCRA INFORMATION: The unused product, in our opinion, is not specifically listed by the EPA as a hazardous waste (40 CFR, Part 261D), nor is it formulated to contain materials which are listed hazardous wastes. It does not exhibit the hazardous characteristics of ignitability, corrosivity, or reactivity and is not formulated with contaminants as determined by the Toxicity Characteristic Leaching Procedure (TCLP). However, used product may be regulated. 14. TRANSPORT INFORMATION USA DOT: NOT REGULATED BY USA DOT. RID/ADR: NOT REGULATED BY RID/ADR. IMO: NOT REGULATED BY IMO. IATA: NOT REGULATED BY IATA. 15. REGULATORY INFORMATION ______ Governmental Inventory Status: All components comply with TSCA, EINECS/ELINCS, AICS, and DSL. EU Labeling: EU labeling not required. U.S. Superfund Amendments and Reauthorization Act (SARA) Title III: This product contains no "EXTREMELY HAZARDOUS SUBSTANCES". SARA (311/312) REPORTABLE HAZARD CATEGORIES: None. This product contains no chemicals reportable under SARA (313) toxic release program. THIS PRODUCT HAS BEEN AUTHORIZED BY USDA FOR USE UNDER THE FOLLOWING CATEGORY: H2 - **Lubricants** With No Food Contact The following product ingredients are cited on the lists below:

ACETONE 67-64-1 1, 10, 11, 15, 18, 19, 20, 21, 23, 25, 26

CHEMICAL NAME

CAS NUMBER LIST CITATIONS

```
1, 10, 20, 21, 23,
                                   115-77-5
1,3-PROPANEDIOL, 2,
                                             25, 26
2-BIS (HYDROXYMETHYL) -
                 --- REGULATORY LISTS SEARCHED ---
         7=IARC 2A 12=TSCA 5a2 17=CA P65 CARC 21=LA RTK
8=IARC 2B 13=TSCA 5e 18=CA RTK
1=ACGIH ALL 6=IARC 1
2=ACGIH A1 7=IARC 2A
          8=IARC 2B 13=TSCA 5e 18=CA RTK
9=OSHA CARC 14=TSCA 6 19=FL RTK
3=ACGIH A2
                                                24=NJ RTK
4=NTP CARC
                      15=TSCA 12b 20=IL RTK
                                                25=PA RTK
5=NTP SUS 10=OSHA Z
                                                 26=RI RTK
Code key: CARC=Carcinogen; SUS=Suspected Carcinogen; REPRO=Reproductive
   16. OTHER INFORMATION
USE: HIGH TEMPERATURE GREASE
      NOTE: MOBIL PRODUCTS ARE NOT FORMULATED TO CONTAIN PCBS.
```

Please call the Customer Response Center on 800-662-4525 for formulation disclosure.

For Internal Use Only: MHC: 1* 1* NA 0* 0*, MPPEC: A, REQ: US - MARKETING, SAFE USE: L

Information given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of the product for particular uses are beyond our control; all risks of use of the product are therefore assumed by the user and WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE IN RESPECT TO THE USE OR SUITABILITY OF THE PRODUCT. Nothing is intended as a recommendation for uses which infringe valid patents or as extending license under valid patents. Appropriate warnings and safe handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, republication or retransmission of this document, in whole or in part, is not permitted. Mobil assumes no responsibility for accuracy of information unless the document is the most current available from an official Mobil distribution system. Mobil neither represents nor warrants that the format, content or product formulas contained in this document comply with the laws of any other country except the United States of America.

Copyright 1996 Mobil Corporation, All rights reserved

