

Section 1

PRODUCT NAME OR NUMBER

LUBRIPLATE No. 100, No. 105, No. 107, No. 110, No. 115

GENERIC/CHEMICAL NAME:

Petroleum Lubricating Grease

Manufacturer's Name

Fiske Brothers Refining Co.

Address

1500 Oakdale Ave., Toledo, Ohio 43605 - 129 Lockwood St., Newark, NJ 07105

FORMULA

Calcium Soap, Mineral Oil and Additives

USDA AUTHORIZATION:

H-2

Emergency Telephone Number

1-800-255-3924 - CHEM-TEL (24 hour)

Telephone Number for Information

419-691-2491 - Toledo Office

Section 2 - Hazardous Ingredients/Identity Information

Hazardous Components

OSHA PEL

ACGIH TLV

Other Limits Recommended

% (optional)

Non-hazardous

Hazardous Material Identification System (HMIS):

Health - 1.

Flammability - 1.

Reactivity - 0

Not a Controlled Product under (WHMIS) - Canada

Special Protection: See Section 9

Section 3 - Health Hazard Data

Threshold Limit Value

5 mg/m³ for oil mist in air. OSHA Regulation 29 CFR 1910.1000

Effects of Overexposure Prolonged or repeated skin contact may cause skin irritation. Product contacting the eyes may cause eye irritation. Human health risks vary from person to person. As a precaution, exposure to liquids, vapors, mists and fumes should be minimized. This product has a low order of acute oral toxicity, but minute amounts aspirated into the lungs during ingestion may cause mild to severe pulmonary injury.

Carcinogenicity:

NTP? No

LARC Monographs? No

OSHA Regulated? No

Section 4 - Emergency and First Aid Procedures

EYE CONTACT: Flush with clear water for 15 minutes or until irritation subsides. If irritation persists, consult a physician.

SKIN CONTACT: Remove any contaminated clothing and wash with soap and warm water. If injected by high pressure under skin, regardless of the appearance or its size, contact a physician IMMEDIATELY. Delay may cause loss of affected part of the body.

<u>INHALATION</u>: Vapor pressure is very low and inhalation at room temperature is not a problem. If overcome by vapor from hot product, immediately remove from exposure and call a physician.

INGESTION: If ingested, call a physician immediately. Do not induce vomiting.

Section 5 - Fire and Explosion Hazard Data

Flash Point (Method Used)

COC - 360°F

Flammable Limits

LEL 0.9%

UEL 7.0%

Extinguishing Media

Foam, Dry Chemical, Carbon Dioxide or Water Spray (Fog)

Special Fire Fighting Procedures

Cool exposed containers with water. Use air-supplied breathing equipment for

enclosed or confined spaces.

Unusual Fire and Explosion Hazards

Do not store or mix with strong oxidants. Empty containers retain residue.

Do not cut, drill, grind, or weld, as they may explode.

PRODUCT NAME OR NUMBER - LUBRIPLATE No. 100, No. 105, No. 107, No. 110, No. 115

Section 6 - Physical/Chemical Characteristics

Boiling Point $>550^{\circ}$ F Specific Gravity (H $_2$ O = 1) 0.89 - 0.93

Vapor Pressure (mm Hg.) <0.01 Melting Point Semi-solid

Vapor Density (AIR = 1) >5 Evaporation Rate <0.01

(Butyl Acetate = 1)

Solubility in Water Negligible

Appearance and Odor Smooth, white grease with mineral oil odor.

Section 7 - Reactivity Data

Stability Unstable Conditions to Avoid N/A

Stable X

Incompatibility (Materials to Avoid) Avoid contact with strong oxidants like liquid chlorine, concentrated oxygen.

Hazardous Decomposition or Byproducts May form SO 2. If incomplete combustion, Carbon Monoxide.

Hazardous Polymerization May Occur Will Not Occur X

May Occur Conditions to Avoid N/A

Section 8 - Spill or Leak Procedures

Steps to be taken in case material is released or spilled

Scrape up grease, wash remainder with suitable petroleum solvent or add absorbent. Keep petroleum products out of sewers and water courses. Advise authorities if product has entered or may enter sewers and water courses.

Waste disposal method

Assure conformity with applicable disposal regulations. Dispose of absorbed material at an approved waste disposal facility or site.

SARA/TITLE III, Section 313 Status - Zinc Compounds - <4%

Section 9 - Special Protection Information

Respiratory Protection (Specify type) Normally not needed

Ventilation Local Exhaust Used to capture fumes and vapors Special N/A

Mechanical (General)

Osed to capture tomes and vapors

Special 1974

Other N/A

Protective Gloves Use oil-resistant gloves, if needed. Eye Protection If chance of eye contact, wear goggles.

Other Protective Equipment Use oil-resistant apron, if needed.

Section 10 - Special Precautions

Precautions to be taken in handling and storing

Keep containers closed when not in use. Do not handle or store near heat, sparks, flame, or strong oxidants.

Other Precautions

Remove oil-soaked clothing and launder before reuse. Cleanse skin thoroughly after contact.

The above information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Fiske Brothers Refining Company. The data on these sheets relates only to the specific material designated herein. Fiske Brothers Refining Company assumes no legal responsibility for use or reliance upon this data.

Date Prepared: January 1, 1996 Prepared by: James R. Kontak