

IDEAS TO GROW WITH®

PO BOX 16458 • FRESNO CA 93755

MATERIAL SAFETY DATA SHEET

PRODUCT/TRADE NAME:

COMPETITOR

I. NAME

PRODUCT/TRADE NAME: COMPETITOR EPA REGISTRATION #: NONE CHEMICAL NAME/COMMON NAME: Ethyl Oleate/Ethyloleate

II. HAZARDOUS INGREDIENTS

CAS# OSHA PEL ACGIH TLV 111-62-6 NE NE

III. PHYSICAL DATA

Ethyloleate

SPECIFIC GRAVITY (H2O = 1): .9
MELTING POINT: NA
VAPOR DENSITY (AIR = 1): NE
% VOLATILES BY VOL.: NE
ODOR: Fatty
APPEARANCE: Amber Liquid
FLASH POINT/METHOD: >150 Deg. C
VAPOR PRESSURE (mmHg): NE
SOLUBILITY IN H2O: Emulsifiable

IV. FIRE & EXPLOSION HAZARD

EXTINGUISHING MEDIA: [] Water Fog [X] Foam []Alcohol Foam [X] CO2 [X] Dry Chemical [] Other FIRE FIGHTING PRECAUTIONS & HAZARDS:

Fight fire upwind. Wear positive pressure self-contained breathing apparatus and full protective clothing. Do not breathe smoke or spray mist. Avoid fallout and runoff. Dike to prevent entering drains, sewers, or water courses. Evacuate people downwind from fire.

V. CARCINOGEN STATUS

[] OSHA [] NTP [] ARC [X] No Listing Type

VI. REACTIVITY

[X] Stable HAZARDOUS POLYMERIZATION
[] Unstable [] May Occur [X] Will Not Occur
AVOID: Strong oxidizers, organic material
HAZARDOUS DECOMPOSITION PRODUCTS: COx

VII. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE OF SPILL: Absorb with inert material and sweep or vacuum into disposal container.

DECONTAMINATION: Treat spill area with detergent and water. Absorb with inert material. Place in disposal container and repeat procedure as necessary until area is clean.

ENVIRONMENTAL HAZARDS: Dike to prevent entering drains, sewers or water courses.

DISPOSAL: Dispose of in accordance with Federal, State and local regulations.

VIII. HEALTH PRECAUTION DATA

INGESTION: Do not ingest. Acute Oral LD50 (Rats) >5000 mg/kg (WECO). Wash thoroughly before eating, drinking or smoking.

INHALATION: No PEL/TLV established for this product. Do not inhale mist. Use proper respiratory protective equipment for exposures encountered.

SKIN ABSORPTION: Acute Dermal LD50 (Rabbits) >5000 mg/kg (WECO). May cause moderate skin irritation. Wear proper personal protective equipment to reduce skin exposure.

EYE EXPOSURE: Keep out of eyes. Minimally irriting to eyes. If exposed, flush eyes for a minimum of 15 minutes with water. Wear proper eye protection to reduce splash exposure.

EFFECTS OF OVEREXPOSURE: Material is not toxic or irritating to the skin. No known chronic effects. No known preexisting medical conditions will be aggravated by exposure.

FIRST AID: In all cases, get prompt medical attention. If ingested, give several glasses of water and induce vomiting. Do not induce vomiting if person is unconscious. For skin exposure, remove contaminated clothing and wash with soap and water. For eye contact, irrigate for a minimum of 15 minutes with water. If inhaled, remove victim to fresh air, and administer CPR if necessary.

IX. SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: Use NIOSH/MSHA - approved respirator for organic vapors for the exposures encountered. Positive pressure self-contained breathing apparatus should be used for confined space entry and excessive exposures.

PERSONAL PROTECTIVE EQUIPMENT: Neoprene or rubber gloves and safety goggles.

13 Chronia | 13 Elammoble

VENTILATION: General ventilation.

X. SPECIAL PRECAUTIONS

Keep out of the reach of children. Read and follow all label instructions.

XI. REGULATORY DATA

SAKA DAZAI	AD OFFICE			[] OHIOHIC [3
]] Pressu	re [] Reactive	[] None	
SARA 313:	[] Yes					
SARA 302:	[] Yes	[X] No	Chemic	al:		
TPQ:						
CERCLA:	[] Yes	[X] No	Chemic	:al:		
RQ:						
RCRA:	[] Yes	[X] No				
NFPA HAZAI	rd ratin	G:		NFPA HAZARD	RATING SO	CALE:
	[1]			0 = Minimal	3 = 9	Serious
Fire:	[1]			1 = Slight		Severe
Reactivity:	[0]			2 = Moderate	, ,	2010.0
Special:	[]					
HMIS CODE	S:			HMIS HAZARD RATING SCALE:		
Health:	[1]			0 = Minimal	3 ≖ 8	Serious
Fire:	[1]			1 = Slight	4 = 3	Severe
Reactivity:	[0]			2 = Moderate		

DATE PREPARED: October 8, 2003 REVISED DATE: July 22, 2005

Notice: This information was developed from information on the constituent materials. No warranty is expressed or implied regarding the completeness or continuing accuracy of the information contained herein, and Wilbur-Ellis disclaims all liability for reliance thereon. The user should satisfy himself that he has all current data relevant to his particular use.

*Technical Material NE - Not Established NA - Not Applicable

24 Hour Emergency Phone Number CHEMTREC: (800) 424-9300

