

Safety Data Sheet



Zep, Inc.
1310 Seaboard Industrial Blvd.
Atlanta, GA 30318
1-877-I-BUY-ZEP (428-9937)
www.zep.com

Section 1. Chemical Product and Company Identification

Product name DYNA 143°
Product use Parts Cleaner Solvent
Product code 0366
Date of issue 06/25/12 **Supersedes** 05/22/09

Emergency Telephone Numbers

For MSDS Information:
Compliance Services 1-877-I-BUY-ZEP (428-9937)

For Medical Emergency
(877) 541-2016 Toll Free - All Calls Recorded

For Transportation Emergency
CHEMTREC: (800) 424-9300 - All Calls Recorded
In the District of Columbia (202) 483-7616

Prepared By

Compliance Services
1420 Seaboard Industrial Blvd.
Atlanta, GA 30318

899



KING COUNTY WTD TRAINING & STORES
1520 SW GRADY WAY
RENTON WA 98057-2951

Section 2. Hazards Identification

Emergency overview

WARNING!

COMBUSTIBLE LIQUID AND VAPOR.

Danger: HARMFUL OR FATAL IF SWALLOWED. CAN ENTER LUNGS AND CAUSE DAMAGE.

*Hazard Determination System (HDS): Health, Flammability, Reactivity

1 2 0

NOTE: MSDS data pertains to the product as delivered in the original shipping container(s). Risk of adverse effects are lessened by following all prescribed safety precautions, including the use of proper personal protective equipment.

Acute Effects

Routes of Entry

Dermal contact. Eye contact. Inhalation.

Eyes May cause eye irritation. Inflammation of the eye is characterized by redness, watering and itching.

Skin May cause skin irritation. Skin inflammation is characterized by itching, scaling, or reddening.

Inhalation No known acute effects of this product resulting from inhalation. Long-term exposure may cause headache, nausea or weakness.

Ingestion Aspiration hazard if swallowed. Can enter lungs and cause damage.

Chronic effects

Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Repeated or prolonged exposure to spray or mist may produce respiratory tract irritation leading to frequent attacks of bronchial infection.

Carcinogenicity

Ingredients: Not listed as carcinogen by OSHA, NTP or IARC.

Product/ingredient name

Not available.

Additional Information: See Toxicological Information (Section 11)

Section 3. Composition/Information on Ingredients

Name of Hazardous Ingredients

Distillates (petroleum), hydrotreated light

CAS number

64742-47-8

% by Weight

90 - 100

Section 4. First Aid Measures

Eye Contact Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.

Skin Contact Flush affected area immediately with large amounts of water for at least 15 minutes. Wash clothing before reuse. Clean shoes thoroughly before reuse. If irritation persists, get medical attention.

Inhalation Move exposed person to fresh air. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing is difficult, Get medical attention.

Ingestion Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. If affected person is conscious, give plenty of water to drink. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Section 5. Fire Fighting Measures

National Fire Protection Association (U.S.A.)



Flash Point	Closed cup: 61.667°C (143°F) [Pensky-Martens.]
Flammable Limits	Lower: 0.7% Upper: 7%
Flammability	COMBUSTIBLE LIQUID AND VAPOR.
Fire hazard	Combustible liquid. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back.
Fire-Fighting Procedures	Use dry chemical, CO ₂ , water spray (fog) or foam.

Section 6. Accidental Release Measures

Spill Clean up Eliminate all ignition sources. Put on appropriate personal protective equipment (see section 8). Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment.

Section 7. Handling and Storage

Handling	Put on appropriate personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Store and use away from heat, sparks, open flame or any other ignition source. Wash thoroughly after handling. Do not reuse container.
Storage	Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Eliminate all ignition sources. Keep container tightly closed and sealed until ready for use. Store between the following temperatures: 40°F - 120°F (4.4°C - 49°C). Keep out of the reach of children.

Section 8. Exposure Controls/Personal Protection

Product name	Exposure limits
---------------------	------------------------

No exposure limit value known.

Personal Protective Equipment (PPE)

Eyes	Safety glasses.	
Body	Wear appropriate protective clothing to prevent skin contact. Recommended: Neoprene gloves. Rubber gloves. Nitrile gloves.	
Respiratory	A respirator is not needed under normal and intended conditions of product use. Use with adequate ventilation. Wear appropriate respirator when ventilation is inadequate.	

Section 9. Physical and Chemical Properties

Physical State	Liquid. [Clear.]	Color	Colorless.
pH	Not applicable.	Odor	Solvent. [Slight]
Boiling Point	192 to 211°C (377.6 to 411.8°F)	Vapor Pressure	0.043 kPa (0.32 mm Hg) [20°C]
Specific Gravity	0.79	Vapor Density	5.4 [Air = 1]
Solubility	Insoluble in the following materials: cold water.	Evaporation Rate	0.14 (Butyl acetate. = 1)
		VOC (Consumer)	100 % (w/w) 6.59 lbs/gal (790 g/l)

Section 10. Stability and Reactivity

Stability and Reactivity	The product is stable.
Incompatibility	Avoid contact with strong oxidizers, excessive heat, sparks or open flame.
Hazardous Polymerization	Under normal conditions of storage and use, hazardous polymerization will not occur.
Hazardous Decomposition Products	carbon oxides (CO, CO ₂)

Section 11. Toxicological Information**Acute Toxicity**

DYNA 143°	LC50 Inhalation Vapor	Rat	>4.3 mg/l	4 hours
	LD50 Dermal	Rabbit	2000 to 4000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-

Section 12. Ecological Information

Environmental Effects Practically non-toxic to aquatic organisms to water solubility. May adsorb to sediments and possibly cause toxic effects to organisms.

Aquatic Ecotoxicity

Distillates (petroleum), hydrotreated light

-

Acute LC50 2200 ug/L Fresh water

Fish - Bluegill - *Lepomis macrochirus* - 4 days
35 to 75 mm**Section 13. Disposal Considerations****Waste Information**

Waste must be disposed of in accordance with federal, state and local environmental control regulations. Consult your local or regional authorities for additional information.

Waste Stream Classification: Non-hazardous waste
Origin: RCRA waste.

Section 14. Transport Information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label
DOT Classification	Not regulated.	-	-	-	
IMDG Class	Not regulated.	-	-	-	

NOTE: DOT classification applies to most package sizes. For specific container size classifications or for size exceptions, refer to the Bill of Lading with your shipment.

PG* : Packing group

Section 15. Regulatory Information**U.S. Federal Regulations**

SARA 313 toxic-chemical notification and release reporting:

No products were found.

Clean Water Act (CWA) 311: No products were found.

Clean Air Act (CAA) 112 regulated toxic substances: No products were found.

All Components of this product are listed or exempt from listing on TSCA Inventory.

State Regulations

California Prop 65 No products were found.

Section 16. Other Information

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

*NOTE: Hazard Determination System (HDS) ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although these ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HDS ratings are to be used with a fully implemented program to relay the meanings of this scale.